



REV	DESCRIPTION	DATE	APPROVED
AO	初版发行	2019.06.27	TSO

- NOTES:
SPECIFICATION:
- CURRENT RATING: 5A MAX
 - VOLTAGE: 100 VAC
 - TEMPERATURE RANGE: -30 °C ~ 85 °C
 - CONTACT RESISTANCE: 40 MILLIONHM MAX
 - INSULATION RESISTANCE: 100 MEGOHMS MIN.
 - INSERTION FORCE : 5N~20N
 - UNMATING FORCE: 8N~20N
 - DURABILITY: 5000 CYCLES

A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

TOLERANCES:	TITLE :
X. ± 0.10	Typec 数据母座-16Pin
.X ± 0.05	PART NO.
.XX ± 0.04	
.XXX ± 0.02	
X. ± 5°	DWG. NAME:
.X ± 3°	
.XX ± 1°	

Hongcheng Technology Co., Ltd.

DRAW:	
(设计)	
CHECK:	
(审核)	
APPD:	
(校对)	

CONNECTOR FRONT EDGE
RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED ±0.05mm